| Ref<br># | Hits    | Search Query                                 | DBs   | Default<br>Operator | Plurals | Time Stamp       |
|----------|---------|--|---|---------------------|---------|------------------|
| 1:1      | 4814079 | release\$3 or remov\$5                       | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT | OR                  | ON      | 2005/07/06 16:32 |
| L2       | 29850   | bead with I1                                 | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT | OR                  | ON      | 2005/07/06 16:32 |
| L3       | 544380  | arm same (rotat\$5 or pivot\$5 or swivel\$3) | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT | OR                  | ON      | 2005/07/06 16:34 |
| L4       | 1397    | 12 and 13                                    | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT | OR                  | ON      | 2005/07/06 16:34 |
| L5       | 140714  | lock\$4 same slot                            | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT | OR                  | ON      | 2005/07/06 16:34 |
| L6       | 160     | I4 and I5 ,                                  | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT | OR                  | ON      | 2005/07/06 16:35 |
| L7       | 97      | I6 and (cylinder or piston)                  | US-PGPUB;<br>USPAT;<br>EPO; JPO;<br>DERWENT | OR                  | ON      | 2005/07/06 16:35 |